

Model	Features	Opto-ASIC	HI-Temp	IP64/IP65 Seal	M12 Option	Brush Servo	Brushless Servo	Stepper	PMDC	NEMA (Small)
15T/H 	<ul style="list-style-type: none"> • Low profile – 1.0" (25.4 mm) height and 1.5" (38 mm) diameter • Thru-bore with sizes up to 0.375" (10 mm) • Simple, innovative flex mounting system • Up to 12 pole commutation optional for brushless motor control • Low temp option down to -40° C • High temp option up to 120° C • Sealing options up to IP64 	✓	✓	✓	✓	✓	✓	✓	✓	
30M 	<ul style="list-style-type: none"> • Compact 30 mm housing • Simple alignment and installation • Up to 1024 CPR (4096 PPR with quadrature counting) • Available with 8-pin molex, 16-pin molex, or M12 connector • Optional 2, 4 or 8-pole commutation • Temperature range -40° to 120° C • Sealing options up to IP69K 	✓	✓	✓	✓	✓	✓	✓		
30MT 	<ul style="list-style-type: none"> • Compact 30 mm housing • Threaded housing for simple installation • Up to 1024 CPR (4096 PPR with quadrature counting) • M12 connector • Temperature range -40° to 120° C • Sealing options up to IP69K 	✓	✓	✓	✓	✓	✓	✓		
121 	<ul style="list-style-type: none"> • Accepts larger shafts up to 0.625" (or 15 mm) • Up to 12 pole commutation available • 0° to 100° C high temperature option • Patented design • Includes IP50 dust seal kit 	✓	✓		✓	✓	✓	✓		
260 	<ul style="list-style-type: none"> • Low profile 1.19" • Thru-bore and hollow bore (blind) styles • Uses EPC's innovative anti-backlash mounting system • Incorporates Opto-ASIC technology • Low temp option down to -40° C • High temp option up to 120° C • Sealing options up to IP64 	✓	✓	✓	✓	✓	✓	✓	✓	✓